


- NOTE:
1. BOTH PUMPS HAVE A 3" VICTAULIC INLET AND A 3" VICTAULIC DISCHARGE.
  2. DIMENSIONS ARE FOR REFERENCE UNLESS OTHERWISE NOTED.

		UNLESS OTHERWISE NOTED LINEAR DIMS. IN INCHES. ANGULAR DIMS. IN DEGREES. TOLERANCES: FRACTIONS DECIMALS ANGULAR .0004/- .0004/+ .0004/- .0004/+ .0004/- .0004/+ .0004/- .0004/+ DO NOT SCALE DRAWING	
		DRAWING NO. _____ CHECKED BY _____ DESIGNER _____ ENGR _____	DRAWING TITLE <b>NH80K2F19E60A TO          SS12519KE60A COMPARISON</b>
T&T PUMP CO. INC. FAIRMONT, WV 26554 NH80K2F19E60A TO SS12519KE60A COMPARISON SCALE non-RELEASE DATE 2-11-08 Sheet 1 of 1	DRAWING NO. _____ CHECKED BY _____ DESIGNER _____ ENGR _____	DRAWING TITLE <b>NH80K2F19E60A TO          SS12519KE60A COMPARISON</b>	T&T PUMP CO. INC. FAIRMONT, WV 26554 NH80K2F19E60A TO SS12519KE60A COMPARISON SCALE non-RELEASE DATE 2-11-08 Sheet 1 of 1